

DELL 34 CURVED VIDEO CONFERENCING MONITOR I C3422WE

Team up. Seamlessly.



COLLABORATE ON A CURVE

Bring your meetings to life with the world's first 34" curved video conferencing monitor certified for Microsoft Teams.[†]



MULTITASK MODE

Multitask efficiently with two PC sources using built-in Picture-by-Picture and Keyboard, Video and Mouse features.



WORK COMFORTABLY

Tilt, swivel and adjust the height of your monitor to your exact preference.



TRUSTED RELIABILITY

As the world's #1 monitor company*, we take pride in our unyielding commitment to quality and the utmost satisfaction of our customers.

World class video conferencing




COLLABORATE ON A CURVE

Join meetings faster: Enjoy world class collaboration and efficient, fast meetings with a dedicated, one-touch Microsoft Teams button.

Immersive collaboration: Razor-sharp video clarity on a pop-up 5MP IR camera with FHD video resolution giving you more than twice the detail of a 2MP on a beautiful, panoramic screen.

Clear, vibrant sound: Dual 5W integrated speakers deliver clear, vibrant communication from any workspace quashing background chatter with a noise-canceling microphone.



ALWAYS MEETING READY

Ready to meet: With the high definition 5MP IR camera, dual 5W integrated speakers and noise-canceling microphone, you are good to go for any meeting. Enhanced Security: The pop-up 5MP camera hides safely out of sight when not in use and adds an intelligent layer of security with facial recognition through Windows Hello™¹.

Personalized convenience: Say what you need and let Cortana do the rest with hands-free commands.



MULTITASK MODE

Multitask efficiently: Connect two PC sources to the monitor and display the content at the same time with Picture-by-Picture (PBP) and Picture-in-Picture (PIP) features. Use the KVM (keyboard, video and mouse) feature to edit content from two different PCs using a single keyboard and mouse.

The power of USB-C®: Connect to productivity: With wired connectivity options like RJ45 and USB-C®, your monitor delivers reliable Ethernet², power, audio and video — all in one clutter-free setup.

Enhanced manageability: Managing your monitor is easy with MAC Address pass-through³, PXE boot, and wake-on LAN conveniently built in.

Productivity at every level: Easy Arrange allows you to easily tile multiple applications across one or more screens with 38 pre-set window partitions and the ability to personalize up to five windows, giving you improved multitasking abilities.⁴



WORK COMFORTABLY

Flexible, all-day comfort: Tilt, swivel and adjust the height of your monitor for a comfortable setup all day long. Or choose from a variety of mounts and stands, including VESA, for even more flexibility.

Easy on the eyes: Comfort meets collaboration with ComfortView Plus⁵ — an always-on, built-in low blue light screen that optimizes eye comfort by reducing potentially harmful blue light emissions while delivering excellent color accuracy.

THANK YOU
FOR MAKING
DELL MONITORS
#1 WORLDWIDE*

Peace of mind: Dell Premium Panel Exchange allows a free panel replacement during the Limited Hardware Warranty⁶ period even if only one bright pixel is found.

Minimize downtime: Your monitor comes with a 3-year Advanced Exchange Service⁷ so that if a replacement becomes necessary, it will be shipped to you the next business day during your 3-year Limited Hardware Warranty.

Get a higher level of support: Upgrade to 24 X 7, in-region technical phone support from qualified engineers with Dell ProSupport option.⁸

Features & Technical Specifications

Monitor

Diagonal Viewing Size
Horizontal
Vertical
Maximum Preset Resolution
Aspect Ratio
Curvature
Pixel Pitch
Pixel Per Inch (PPI)
Brightness
Color Support

Contrast Ratio
Viewing Angle

Response Time
Panel Type
Backlight Technology
PbP / PiP / KVM
Dell Display Manager Compatibility
Daisy Chain Availability
Remote Asset Management
Display Screen Coating

Connectivity

Connectors

Video Conferencing

Webcam Specs

Built-in Microphone
Built-in Speaker

Design Features

Adjustability

Security
Flat Panel Mount Interface

Power

Voltage Required
Power Delivery (via USB-C Type C)
Power Consumption (Operational)
Power Consumption Stand by/Sleep
Dimensions (with Stand)

Height (Compressed~Extended)
Width
Depth

Weight

Weight (Panel Only - for VESA Mount)
Weight (with Packaging)

Standard Service Plan

Optional Service Plan

Environmental Compliance

Dell 34 Curved Video Conferencing Monitor – C3422WE

867.1 mm (34.14 inches)
799.8 mm (31.49 inches)
334.8 mm (13.18 inches)
3440 x 1440 at 60Hz
21:9
3800R (typical)
0.2325 mm x 0.2325 mm
109.68
300 cd/m² (typical)
Color Gamut (typical): 99% sRGB
Color Depth: 1.07 billion colors
1000:1 (typical)
178° (vertical) typical
178° (horizontal) typical
8 ms (Normal); 5 ms (Fast) - (gray to gray)
In-Plane Switching Technology
LED
PbP (Yes) / PiP (Yes) / KVM (Yes), Auto KVM
Yes
No
Yes, via Dell Command I Monitor
Antiglare with 3H hardness

1 x DP 1.2 (HDCP2.2); 1 x HDMI 2.0 (HDCP2.2); 1 x USB Type-B (USB 3.2 Gen1 upstream port); 1 x USB Type-C^{*} (Alternate mode with DisplayPort 1.2, USB 3.2 Gen1 upstream port, Power Delivery up to 90W); 1 x USB Type-C downstream (15W), USB 3.2 Gen1 (5Gbps); 2 x super speed USB 5Gbps (USB 3.2 Gen1); 1 x super speed USB 5Gbps (USB 3.2 Gen1) with BC 1.2 charging capability at 2 A (max); 1 x 3.5 mm headphone jack; 1 x RJ45

5 mega-pixel RGB+IR, Windows Hello™¹ compatible
Video Frame Rate - 1920x 1080 (Full HD) - up to 30 frames per second
Digital microphone x2
2 x 5W

Height-adjustable stand (120 mm), Tilt (-5° to 21°)
Swivel (-30° to 30°), Slant adjust -4° to 4°
Security lock slot (cable lock sold separately)
VESA (100 mm)

100-240 VAC / 50 or 60 Hz ± 3 Hz / 2.8 A (maximum)
Up to 90W
38 W (On Mode)⁹ / 220 W (Max)¹⁰
0.5 W

456.20 mm ~ 576.2 mm (17.96 inches ~ 22.68 inches)
815.85 mm (32.1 inches)
234.95 mm (9.30 inches)

7.3 kg (16.06 lb)
16 kg (35.2 lb)

Premium Panel Exchange, 3-Years Advanced Exchange Service⁷ and Limited Hardware Warranty⁶

Dell ProSupport⁸

ENERGY STAR[®] certified monitor, EPEAT[®] Gold registered where applicable¹¹, TCO Certified Display, RoHS Compliant, BFR/PVC Free monitor (excluding external cables), meets NFPA 99 leakage current requirements, arsenic-free glass and mercury-free for the panel only

What's in the box?

Components

- Monitor withstand

Cables

- Power cable
- 1xDP Cable(DPtoDP)
- 1xUSB Type-Ccable(C to C)
- 1xUSB 3.2Gen1Type-A to Type-B upstream cable

Documentation

- Quick Setup Guide
- Safety and Regulatory Information



Sales@UniLinkinc.com | www.UniLinkinc.com | 800.666.2980