DELL P3221D 80 cm (31.5") 2560 x 1440 pixels Quad HD LCD Black



Brand : DELL

Product code: DELL-P3221D

Product name : P3221D

- 80cm (31.5") Quad HD 2560 x 1440 LED IPS
- 8ms, 16:9, 350cd/m², 1000:1
- USB, HDMI, DisplayPort

80cm (31.5") Quad HD 2560 x 1440 LED IPS, 16:9, 350cd/m², 1.07B, 8ms, 178°/178°, 1000:1



DELL P3221D 80 cm (31.5") 2560 x 1440 pixels Quad HD LCD Black:

Our first 32" QHD 2560 X 1440 P Series monitor delivers more on-screen real estate than Full HD, in a new, sleek design.
DELL P3221D. Display diagonal: 80 cm (31.5"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 2.0 / 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black

Display	
Display diagonal *	80 cm (31.5")
Display brightness (typical)	350 cd/m²
Display resolution *	2560 x 1440 pixels
Native aspect ratio *	16:9
Response time	8 ms
HD type *	Quad HD
Display technology *	LCD
Backlight type	LED
Screen shape *	Flat
Supported graphics resolutions	640 x 480 (VGA),720 x 400,800 x 600 (SVGA),1024 x 768 (XGA),1152 x 864 (XGA+),1280 x 1024 (SXGA),1280 x 800 (WXGA),1280 x 800,1600 x 1200 (UXGA),1680 x 1050 (WSXGA+),1920 x 1080 (HD 1080),1920 x 1200 (WUXGA),2048 x 1080,2560 x 1440
Supported video modes	480i,480p,576i,576p,720p,1080i,1080p,1440p
Contrast ratio (typical) *	1000:1
Maximum refresh rate *	60 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	1.07 billion colours
Panel type *	IPS
Response time (fast)	5 ms
Pixel pitch	0.2727 x 0.2727 mm
Pixel density	93.24 ppi
Horizontal scan range	30 - 90 kHz
Vertical scan range	56 - 76 Hz
Viewable size, horizontal	69.8 cm
Viewable size, vertical	39.3 cm
Viewable size diagonal	80.1 cm

Performance	
NVIDIA G-SYNC *	✗
AMD FreeSync *	✗

Multimedia	
Built-in speaker(s) *	✗

Ergonomics	
Cable lock slot *	✓
VESA mounting *	✓
Height adjustment *	✓
Height adjustment	15 cm
Pivot	✓
Pivot angle	-90 - 90°
Swivelling	✓
Swivel angle range	-30 - 30°
Tiltable	✓
Tilt angle range	-5 - 21°

Power	
Energy efficiency class (SDR) *	E
Energy consumption (SDR) per 1000 hours *	25 kWh
Power consumption (typical) *	25.1 W
Power consumption (standby) *	0.2 W
Power consumption (max)	145 W
Power consumption (off)	0.2 W
Power consumption (PowerSave)	20.6 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Energy efficiency scale	A to G

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	5 - 90%

Sustainability	
Sustainability certificates	ENERGY STAR

Multimedia	
Built-in camera *	✗

Design	
Market positioning *	Business
Product colour *	Black
Feet colour	Silver

Ports & interfaces	
Built-in USB hub *	✓
USB hub version	2.0 / 3.2 Gen 1 (3.1 Gen
USB upstream port type	1) USB Type-C
Number of upstream ports	1
USB Type-A downstream ports quantity	4
DVI port	✗
HDMI *	✓
HDMI ports quantity	1
DisplayPorts quantity	1
Audio input	✗
Headphone out *	✗

Weight & dimensions	
Width (with stand)	713.4
Depth (with stand)	mm 230
Height (with stand)	mm
Weight (with stand)	618.8
Width (without stand)	mm 10.7
Depth (without stand)	kg 71.3
Height (without stand)	cm 5.53
Weight (without stand)	cm 41.8
Bezel width (side)	cm 6.4
Bezel width (top)	kg
Bezel width (bottom)	7.6 mm
	7.5 mm
	1.79 cm

Packaging data	
Package width	940
Package depth	mm
Package height	177
Package weight	mm
	525
	mm
	15.6 kg

Publication date: 29-NOV-2021. Prints or copies of Information are only valid on the printed Publication date

UniLink
Sales@UniLinkinc.com | www.UniLinkinc.com | 800.666.2980