

Lexmark™

Lexmark XM3142

Scalable solutions. Enterprise-level security.



Lexmark XM3142

The LexmarkXM3142 monochrome all-in-one brings scalable solution support and enterprise-level security to small workgroups at up to 42 ppm*. Compactsize with Trusted Platform Module (TPM) standard.** Print release capability and managed print services (MPS) eligibility. Large easy-to-use touchscreen provides consistent performance across fleet. Print from anywhere with standard Wi-Fi and full mobile support.



Scalable solutions increase efficiency and savings

- Monochromeall-in-one with Trusted Platform Module(TPM) standard.**
- With the embedded solutions framework on the XM3142, you can add Lexmark or other supported solutions, including third-party print release with badge reader.
- Large easy-to-use touchscreen provides consistent performanceacross fleet.

The right fit for your customers' businesses

- Compact size integrates seamlesslyinto tightspaces in your work environment.
- Provides security and solutions to meet the stringent requirements of different industries.
- Managed print services (MPS) capabilities make this all-in-one a perfect addition to your printer fleet.

Stay protected with enterprise-level security

- Lexmark printers and all-in-ones are designed to help protect your data, your device, and your network.
- Includes standard Trusted Platform Module** that stores encryption keys on separate hardware from the data, along with authentication and system integrity checks.
- Many banks, healthcare clients and schools trust Lexmark security over all others in the industry.

Easy to manage without burden on IT staff

- Sensors continuously monitor hundreds of data pointsthat provide added benefits, like predictive service and automatic supplies replenishment, when connected to LexmarkCloud Services.
- Lexmark Cloud Fleet Management (CFM) makes it possibleto remotely monitor, manage and secure your print environment. This increases uptime, plus you get access to new solutions and workflows through the cloud.

Focus on business instead of printers

- You can count on the high performance of the XM3142with fast print speeds up to 42 ppm*and single-pass two-sided scan speeds of 96 ipm.
- Print from anywhere with standard Wi-Fi and full mobile support.
- Steel frames provide durabilityand long-life reliability from the front office tothe warehouse.

Working for the environment

- Automatic two-sided printing is standard, along with built-in energy-saving modes that help support ratings of EPEAT® Silver and ENERGY STAR® certified.
- Keep toner cartridges out of landfills with the Lexmark Cartridge Collection Program (LCCP) that supports reuse and recycling (availability varies by country).

* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.
** The Trusted Platform Module (TPM) is not available in some countries.

Lexmark XM3142



P/N	
	Hardware
	Lexmark XM3142
29S8150	**Supplies**
	Lexmark XM3142 18K Toner Car tridge
P/N	
24B7535	Lexmark MS/MX331, 431, MX432, B3340, B/MB3442, M/XM1342 40K Imaging Unit
55B0ZA0	**Paper Handling**
P/N	550-Sheet Tray
29S0600	550-Sheet Lockable Tray
29S0800	**Memory Options**
	Intelligent Storage Device (ISD)
P/N	**Application Solutions**
57X9528	Desktop Contactless Reader
P/N	Contactless Front Solutions
57 X0225	Module (Primary)
57 X0235	Contact Authentication Device
	Contactless Authentication Device
57 X0300	IPDS License
57 X0301	Bar Code License
	Connectivity
82S1203	USB Cable (2-meter)
82S1204	Surge Protective Device, 110-120V
P/N	**Furniture**
1021294	Swivel Cabinet
SPD0001	Adjustable Printer Stand
P/N	
3073173	
35S8502	

1 Multifunction product with 4.3-inch (10.9 cm) touch screen
13.9x16.2 x 14.2in.
353.60x411.48x360.68 mm

2 150-Sheet output bin

3 Dimensions included as part of base model

100-Sheet multipurpose feeder

Dimensions included as part of base model

4 250-Sheet tray
Dimensionsincluded as part of base model

5 550-Sheet Tray
4.2 x 14.6 x 14.9 in.
107 x 370 x 378 mm

Standard

Optional

Supports one optional 550-sheet tray.
All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at https://publications.lexmark.com/publications/furniture_safety/

Product Specifications	Lexmark XM3142
Printing	
Display	Lexmark e-Task 4.3-inch color touch screen
Print Speed	Up to:Black: 42 ppm[1](Letter)
Time to First Page	As fast as:Black: 5.9 seconds
Print Resolution	Black: 1200 x 1200 dpi, 2400 IQ (2400 x 600 dpi), 300 x 300 dpi, 600 x 600 dpi, 1200 IQ (1200 x 600 dpi)
Memory	Standard: 2 GB / Maximum: 2 GB
Hard Disk	Intelligent Storage Drive (optional)
Recommended Monthly Page Volume	800 - 8,000 pages[2]
Maximum Monthly Duty Cycle	Up to: 80,000 pages per month[3]
Copying	
Copy Speed	Up to:Black: 42 cpm[1](Letter)
Time to First Copy	As fast as:Black: 5.9 seconds
Scanning	
Scanner Type / ADF Scan	Flatbed scanner with automatic document feeder / DADF (single pass Duplex)
A4/Ltr Duplex Scan Speed	Up to:Black: 92/96 sides per minute / Color: 40/42 sides per minute
A4/Ltr Simplex Scan Speed	Up to:Black: 46/48 sides per minute / Color: 20/21 sides per minute
ADF Paper Input Capacity	Up to: 50 pages 20 lb or 75 gsm bond
Faxing	
Modem Speed	ITU T.30, V.34 Half-Duplex, 33.6 Kbps
Supplies [4]	up to: 18,000[5]-page Black Cartridge
Laser Cartridge Yields	Up to: 40,000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage
Imaging Unit Estimated Yield	3,000[5]-page Black Return Program Toner Cartridge[5]
Cartridge(s) Shipping with Product	
Paper Handling	100-Sheet Multipurpose Feeder, Integrated Duplex, 150-Sheet Output Bin, 250-Sheet Input 550-Sheet Lockable Tray, 550-Sheet Tray
Included Paper Handling	Up to:Standard: 350 pages 20 lb or 75 gsm bond / Maximum: 900 pages 20 lb or 75 gsm bond
Optional Paper Handling	Up to:Standard: 150 pages 20 lb or 75 gsm bond / Maximum: 150 pages 20 lb or 75 gsm bond
Paper Input Capacity	Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Specialty Media Guide
Paper Output Capacity	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Hagaki Card, Letter, B5 Envelope, Statement, C5 Envelope, Executive, DL Envelope, Folio, 10 Envelope
Media Types Supported	
Media Sizes Supported	
General Information[6]	Gigabit Ethernet (10/100/1000), USB Compatible with USB 2.0 Specification (Type B), Front USB 2.0 Specification Hi-Speed Certified port (Type A)
Standard Ports	Operating:53 dBA (Print) / 58 dBA (Copy) / 56 dBA (Scan)
Noise Level	Temperature: 10 to 32°C (50 to 90°F) / Altitude: 0 - 2896 Meters (9,500 Feet) / Humidity: 15 to 80% Relative Humidity
Specified Operating Environment	See Statement of Limited Warranty: 1-Year Onsite Service, Next Business Day
Limited Warranty	H x W x D: 13.9 x 16.2 x 14.2 in. / 30 lb.
Size / Weight	TEC: 0.52 kilowatt-hours per week
ENERGY STAR Typical Electricity Consumption	

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

[1] Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.
"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.[3]"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.[4]Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.[5]Average yield based on approximately 5% print coverage.

[6] Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

©2022 Lexmark. All rights reserved.
Lexmark, Markvision and the Lexmark logo are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries and regions. Mopria®, the Mopria® Logo, and the Mopria Alliance™ word mark and logo are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited.ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT is a trademark ofthe Green Electronics Councilin the United States and other countries. All other trademarks are the property of their respective owners.