SAMSUNG

UniLink™

Crystal UHD Signage

QHC Series

Slim design.
Stunning performance.

Introducing the QHC series, the slimmest display in the Samsung's UHD signage offerings. This products deliver an unparalleled slim design that fits into any business, while delivering the visual quality to make a big impact. The sleek form factor is easily installed to fit any room design and delivers stunning visual performance. Dynamic Crystal Color and Quantum Processor Lite 4K delivering consistent, lifelike colors to any content. This is not just a display for simple advertising. It's a display that brings the solutions, tools, and picture quality to grow to your business, no matter what industry you're in.

Key features

Ultra Slim Depth
The unparalleled ultra-slim thickness of 28.5mm makes it the thinnest option in Samsung's UHD Signage series. It comes with the Slim Fit Wall Mount, which allows you to install it neatly and easily in any environment.

Even Bezels and Centered VESA Holes
The bezels are even on all four sides of the display for a consistent look, while the central VESA mounting holes ensure secure mounting and easy adjustability to portrait mode.

Dynamic Crystal Color
One billion shades of color let you see every subtlety with lifelike color variations. Images are clear and consistent thanks to Samsung's industry leading video processing and upscaling technology.

Smartview+
In the QHC series, SmartView+ enables wireless screen sharing for easy collaboration and quick screen switching with just a click.

Smart Calibration
Guarantee complete brand consistency across every location. Using the Samsung mobile app, calibrate displays to showcase brand logos and other collateral in the exact colors required.

Energy star / EPEAT Bronze
Samsung is making diverse efforts to reduce our environmental impact in smart signage, and encouraging users to pursue a more sustainable life.

Specif ications

Model			QH43C	QH50C	QH55C	QH65C	QH75C
Display Panel	Diagonal Size	Class	43	50	55	65	75
		Measured	42.5	48.5	54.6	64.5	74.5
	Resolution		3,840 x 2,160 (16:9)	3,840 x 2160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)
	Brightness (Typ.)		700 nit	700 nit	700 nit	700 nit	700 nit
	Orientation		Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait
	Haze		25%	25%	25%	25%	25%
	Contrast Ratio (Typ.)		4,000:1	4,000:1	4,000:1	4,000:1	4,000:1
	Type		VA	VA	VA	VA	VA
	Active Display Area		941.184 (H) x 529.416 (V)	1,095.84 (H) x 616.41 (V)	1,209.6 (H) x 680.4 (V)	1,428.48 (H) x 803.52 (V)	1,650.24 (H) x 928.26 (V)
	Pixel Pitch (mm)		0.245 x 0.245	0.285 x 0.285	0.315 x 0.315	0.372 x 0.372	0.429 x 0.429
	Color Gamut		NTSC 72%	NTSC 72%	NTSC 72%	NTSC 72%	NTSC 72%
	Operation Hour		24/7	24/7	24/7	24/7	24/7
Connectivity / Sound	Input	Video	DP 1.2 (1), HDMI 2.0 (3)	DP 1.2 (1), HDMI 2.0 (3)	DP 1.2 (1), HDMI 2.0 (3)	DP 1.2 (1), HDMI 2.0 (3)	DP 1.2 (1), HDMI 2.0 (3)
		Audio	N/A	N/A	N/A	N/A	N/A
		USB	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2
		Tuner	N/A	N/A	N/A	N/A	N/A
	Output	Video	N/A	N/A	N/A	N/A	N/A
		Audio	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack
		USB	N/A	N/A	N/A	N/A	N/A
	WiFi / BT		O/O	O/O	O/O	O/O	O/O
	External Control		RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45
	Speaker		10W 2ch	10W 2ch	10W 2ch	10W 2ch	10W 2ch
Mechanical Spec	Dimension (mm / in.)	Set	969.5 x 557.8 x 28.5 mm / 38.2 x 22 x 1.1 in.	1,124.1 x 644.8 x 28.5 mm / 44.3 x 25.4 x 1.1 in.	1,237.9 x 708.8 x 28.5 mm / 48.7 x 27.9 x 1.1 in.	1,456.8 x 831.9 x 28.5 mm / 57.4 x 32.8 x 1.1 in.	1,682.3 x 960.4 x 28.5 mm / 66.2 x37.8 x 1.1 in.
		Package	1,093 x 667 x 126 mm / 43 x 26.3 x 5 in.	1,246 x 761 x 131 mm / 49 x 30 x 5.2 in.	1,403 x 835 x 148 mm / 55.2 x 32.9 x 5.8 in.	1,616 x 945 x 164 mm / 63.6 x 37.2 x 6.5 in.	1,839 x 1,113 x 180 mm / 72.4 x 43.8 x 7 in.
	Weight (kg / lbs.)	Set	9.3 kg / 20.5 lbs.	12.4 kg / 27.3 lbs.	16.9 kg / 37.3 lbs.	22.4 kg / 49.4 lbs.	34.2 kg / 75.4 lbs.
		Package	11.8 kg / 26 lbs.	15.5 kg / 34.2 lbs.	21.1 kg / 46.5 lbs.	29.8 kg / 65.7 lbs.	44 kg / 97 lbs.
	VESA Mount		200 x 200	200 x 200	200 x 200	200 x 300	400 x 400
	VESA Mount Screw (Min~Max)		M8, 12~14mm	M8, 12~14mm	M8, 12~14mm	M8, 12~14mm	M8, 12~14mm
	Bezel Width (mm)		11.5 (Even)	11.5 (Even)	11.5 (Even)	11.5 (Even)	13.4 (Even)
Features	Key		UHD Signage with Built-in MagicInfo S10, SSSP 10.0	UHD Signage with Built-in MagicInfo S10, SSSP 10.0	UHD Signage with Built-in MagicInfo S10, SSSP 10.0	UHD Signage with Built-in MagicInfo S10, SSSP 10.0	UHD Signage with Built-in MagicInfo S10, SSSP 10.0
	Internal Player	Operating System	Tizen 7.0	Tizen 7.0	Tizen 7.0	Tizen 7.0	Tizen 7.0
		Processor	CA73 1.6GHz Quad-Core	CA73 1.6GHz Quad-Core	CA73 1.6GHz Quad-Core	CA73 1.6GHz Quad-Core	CA73 1.6GHz Quad-Core
		Storage (FDM)	16GB (10GB available)	16GB (10GB available)	16GB (10GB available)	16GB (10GB available)	16GB (10GB available)
	Special	H/W	2nd Gen. B2B Design Center IR Temperature Sensor Ambient Sensor Auto Level Wi-Fi(2.4/5.0GHz dual) and BT	2nd Gen. B2B Design Center IR Temperature Sensor Ambient Sensor Auto Level Wi-Fi(2.4/5.0GHz dual) and BT	2nd Gen. B2B Design Center IR Temperature Sensor Ambient Sensor Auto Level Wi-Fi(2.4/5.0GHz dual) and BT	2nd Gen. B2B Design Center IR Temperature Sensor Ambient Sensor Auto Level Wi-Fi(2.4/5.0GHz dual) and BT	2nd Gen. B2B Design Center IR Temperature Sensor Ambient Sensor Auto Level Wi-Fi(2.4/5.0GHz dual) and BT
		S/W	Signage New Home Workspace (Microsoft377/VMWare/RDP) Custom Home Auto Source Switching and Recovery Dicom Simulation Mode Director Mode SmartView+ Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration	Signage New Home Workspace (Microsoft377/VMWare/RDP) Custom Home Auto Source Switching and Recovery Dicom Simulation Mode Director Mode SmartView+ Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration	Signage New Home Workspace (Microsoft377/VMWare/RDP) Custom Home Auto Source Switching and Recovery Dicom Simulation Mode Director Mode SmartView+ Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration	Signage New Home Workspace (Microsoft377/VMWare/RDP) Custom Home Auto Source Switching and Recovery Dicom Simulation Mode Director Mode SmartView+ Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration	Signage New Home Workspace (Microsoft377/VMWare/RDP) Custom Home Auto Source Switching and Recovery Dicom Simulation Mode Director Mode SmartView+ Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration
Certification	Safety		60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1
	EMC		Class B	Class B	Class B	Class B	Class B
	Environment		ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT
	IP Rating		IP5x	IP5x	IP5x	IP5x	IP5x
	Security		802.1 x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	802.1 x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	802.1 x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	802.1 x(WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	802.1 x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP
	Power Supply		AC 100 - 240 V, 50/60 Hz	AC 100 - 240 V, 50/60 Hz	AC 100 - 240 V, 50/60 Hz	AC 100 - 240 V, 50/60 Hz	AC 100 - 240 V, 50/60 Hz
Power	Power Consumption	Max [W/h]	TBD	TBD	TBD	TBD	TBD
		Typical [W/h]	TBD	TBD	TBD	TBD	TBD
		Sleep mode	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W
Operating Condition	Temperature		0℃~ 40℃	0℃~ 40℃	0℃~ 40℃	0℃~ 40℃	0℃~ 40℃
	Relative Humidity		10~80%	10~80%	10~80%	10~80%	10~80%
Accessories	Included		Quick Setup Guide, Warranty Card, Power Cord RS232C (In) Gender	Quick Setup Guide, Warranty Card, Power Cord RS232C (In) Gender	Quick Setup Guide, Warranty Card, Power Cord RS232C (In) Gender	Quick Setup Guide, Warranty Card, Power Cord RS232C (In) Gender	Quick Setup Guide, Warranty Card, Power Cord RS232C (In) Gender
	Optional	Stand	Remote Controller and Batteries	Remote Controller and Batteries	Remote Controller and Batteries	Remote Controller and Batteries	Remote Controller and Batteries
		Mount	STN-L4355C	STN-L4355C	STN-L4355C	STN-L6585C	STN-L6585C
		Specialty	WMN-B50SC	WMN-B50SC	WMN-B50SC	WMN-B50SC	WMN-B50SC
			TBD	TBD	TBD	TBD	TBD

SAMSUNG

youtube.com/samsungbizusa @SamsungBizUSA

UniLink

Sales@UniLinkinc.com | www.UniLinkinc.com | 800.666.2980

©2023 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. Specifications and design are subject to change without notice. Non-metric weights and measurements are approximate. Simulated screen images. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. See samsung.com for detailed information. Printed in USA. DIGSIGQHC LEAFLET-JULTK