

Product availability: Stock - Normally stocked in distribution facility



### Overview

Lead time	Usually in Stock
-----------	------------------

### Main

Main Input Voltage	120 V
Output voltage	120 V
Kw Rating	330 W
Rated power in VA	600 VA
Product or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA 5-15P
Output connection type	5 NEMA 5-15R 2 NEMA 5-15R surge
Cable length	5 Ft (1.52 m)
Battery Type	Lead-Acid battery
Provided equipment	User Manual

### Batteries & Runtime

Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	10 H
RBC Quantity	1
Battery Charge Power (Watts)	7 W rated
Battery power in VAH	78 VAh capacity 66 VAh runtime
Battery Life	3...5 Year(S)
Extendable Run Time	0

## General

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

## Physical

Height	5.47 In (13.9 cm)
Width	10.79 In (27.4 cm)
Depth	4.13 In (10.5 cm)
Net Weight	7.69 Lb(US) (3.49 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Efficiency at full load	92...139 V

## Output

Max Configurable Power (Watts)	330 W
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
Topology	Standby
Wave type	Stepped approximation to a sinewave
Maximum configurable power in VA	600 VA
Transfer Time	6ms typical : 10ms maximum

## Conformance

Product Certifications	California (CEC) Battery Charger[RETURN]cTUVus[RETURN]NOM
Equipment protection policy	Lifetime : \$75000

## Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...90 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 Ft (0.00...15240.00 m)
Acoustic level	35 dBA
Heat dissipation	16 Btu/H

## Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge energy rating	490 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m
Let Through Voltage Rating	5 V

## Ordering and shipping details

Category	11309-APC RESALE PRODUCTS
Discount Schedule	APC1
GTIN	731304325116
Returnability	No

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.72 In (19.6 cm)
Package 1 Width	6.61 In (16.8 cm)
Package 1 Length	14.29 In (36.3 cm)
Package 1 Weight	8.40 Lb(US) (3.81 kg)
SCC14	10731304325113

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------

Product Life Status : **Commercialised**



Sales@UniLinkinc.com | [www.UniLinkinc.com](http://www.UniLinkinc.com) | 800.666.2980