



APC Back-UPS 600VA, 120V, 1 USB charging port, 7 NEMA outlets (2 surge)

BE600M1

Overview

Lead Time Usually in Stock

Main

| | |
|---------------------------|------------------------------------|
| Main Input Voltage | 120 V |
| Main Output Voltage | 120 V |
| Kw Rating | 330 W |
| Rated Power In Va | 600 VA |
| Product Or Component Type | Uninterruptible power supply (UPS) |
| Input Connection Type | NEMA 5-15P |
| Output Connection Type | 5 NEMA 5-15R 2 NEMA 5-15R surge |
| Cable Length | 5 ft (1.52 m) |
| Battery Type | Lead-Acid battery |
| Provided Equipment | User Manual |

Batteries & Runtime

| | |
|------------------------------|---------------------------------------|
| Run Time | View Runtime Graph |
| Efficiency | View Efficiency Graph |
| Included Battery Modules | 0 |
| Battery Slots Empty | 0 |
| Typical Recharge Time | 10 h |
| Rbc Quantity | 1 |
| Battery Charge Power (Watts) | 7 W rated |
| Battery Power In Vah | 78 VAh capacity 66 VAh runtime |
| Battery Life | 3...5 year(s) |
| Replacement Battery | APCRBC154 |
| Extendable Run Time | 0 |

General

| | |
|-------------------------------------|---|
| Number Of Power Module Free Slots | 0 |
| Number Of Power Module Filled Slots | 0 |

Redundant No

Physical

| | |
|---------------------|-----------------------|
| Height | 5.47 in (13.9 cm) |
| Width | 10.79 in (27.4 cm) |
| Depth | 4.13 in (10.5 cm) |
| Net Weight | 7.69 lb(US) (3.49 kg) |
| Mounting Preference | No preference |
| Mounting Mode | Not rack-mountable |
| Two Post Mountable | 0 |
| Usb Compatible | No |

Input

| | |
|-------------------------|--------------------------------|
| Input Frequency | 50/60 Hz +/- 3 Hz auto-sensing |
| Efficiency At Full Load | 92...139 V |

Output

| | |
|----------------------------------|-------------------------------------|
| Max Configurable Power (Watts) | 330 W |
| Output Frequency (Sync To Mains) | 50/60 Hz +/- 3 Hz sync to mains |
| Topology | Standby |
| Wave Type | Stepped approximation to a sinewave |
| Maximum Configurable Power In Va | 600 VA |
| Transfer Time | 6ms typical : 10ms maximum |

Conformance

| | |
|-----------------------------|---|
| Product Certifications | California (CEC) Battery Charger cTUVus NOM |
| Equipment Protection Policy | Lifetime : \$75000 |

Environmental

| | |
|---------------------------------------|----------------------------------|
| Ambient Air Temperature For Operation | 32...104 °F (0...40 °C) |
| Relative Humidity | 0...90 % |
| Operating Altitude | 0...10000 ft |
| Ambient Air Temperature For Storage | 5...113 °F (-15...45 °C) |
| Storage Relative Humidity | 0...95 % |
| Storage Altitude | 0...50000 ft (0.00...15240.00 m) |
| Acoustic Level | 35 dBA |
| Heat Dissipation | 16 Btu/h |

Communications & Management

| | |
|---------------|--|
| Control Panel | LED status display with on line : on battery : replace battery and overload indicators |
|---------------|--|

Alarm Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

| | |
|-----------------------------------|--|
| Surge Energy Rating | 490 J |
| Filtering | Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m |
| Let Through Voltage Rating | 5 V |

Ordering and shipping details

| | |
|--------------------------|---------------------------|
| Category | 11309-APC RESALE PRODUCTS |
| Discount Schedule | APC1 |
| Gtin | 731304325116 |
| Returnability | No |

Packing Units

| | |
|-------------------------------------|-----------------------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 7.72 in (19.6 cm) |
| Package 1 Width | 6.61 in (16.8 cm) |
| Package 1 Length | 14.29 in (36.3 cm) |
| Package 1 Weight | 8.40 lb(US) (3.81 kg) |
| Scs14 | 10731304325113 |

Contractual warranty

| | |
|-----------------|---------------------------|
| Warranty | 3 years repair or replace |
|-----------------|---------------------------|


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)




Energy Efficient Take-back Transparency RoHS/REACH


Resource performance

 Energy Efficient Product

 Take-Back Program Available

Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)

California Proposition 65 **WARNING:** This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



Sales@UniLinkinc.com | www.UniLinkinc.com | 800.666.2980