



APC Smart-UPS, Line Interactive, 1500VA, Tower, 120V, 8x NEMA 5-15R outlets, SmartConnect Port+SmartSlot, AVR, LCD

SMT1500C

Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead Time	Usually Ships within 2 Weeks

Main

Main Input Voltage	120 V
Other Input Voltage	110 V 125 V
Main Output Voltage	120 V
Other Output Voltage	110 V 125 V
Kw Rating	1000 W
Rated Power In Va	1440 VA
Input Connection Type	NEMA 5-15P
Output Connection Type	8 NEMA 5-15R
Cable Length	6 ft (1.83 m)
Number Of Cables	1
Battery Type	Lead-Acid battery
Provided Equipment	Installation guide USB cable

Complementary

Software Package	SmartConnect software for remote power monitoring feature availability varies by terms of use
-------------------------	---

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Extendable Run Time	0
Included Battery Modules	0
Battery Slots Empty	0
Typical Recharge Time	3 h
Rbc Quantity	1
Battery Life	3...5 year(s)

Battery Charge Power (Watts)	136 W rated
------------------------------	-------------

General

Number Of Power Module Filled Slots	0
-------------------------------------	---

Number Of Power Module Free Slots	0
-----------------------------------	---

Product Web Sub-Family	Cloud-enabled monitoring
------------------------	--------------------------

Redundant	No
-----------	----

Physical

Color	Black
-------	-------

Height	8.62 in (21.9 cm)
--------	-------------------

Width	6.73 in (17.1 cm)
-------	-------------------

Depth	17.28 in (43.9 cm)
-------	--------------------

Net Weight	54.23 lb(US) (24.6 kg)
------------	------------------------

Mounting Location	Front
-------------------	-------

Mounting Preference	No preference
---------------------	---------------

Mounting Mode	Not rack-mountable
---------------	--------------------

Two Post Mountable	0
--------------------	---

Usb Compatible	Yes
----------------	-----

Input

Efficiency At Full Load	75...154 V adjustable 82...144 V
-------------------------	-------------------------------------

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
-----------------	--------------------------------

Output

Harmonic Distortion	Less than 5%
---------------------	--------------

Maximum Configurable Power In Va	1440 VA
----------------------------------	---------

Max Configurable Power (Watts)	1000 W
--------------------------------	--------

Transfer Time	6ms typical : 10ms maximum
---------------	----------------------------

Topology	Line Interactive
----------	------------------

Wave Type	Sine wave
-----------	-----------

Output Frequency (Sync To Mains)	50/60 Hz +/- 3 Hz sync to mains
----------------------------------	---------------------------------

Conformance

Product Certifications	cULus ENERGY STAR V2.0 (USA)
------------------------	---------------------------------

Equipment Protection Policy	Lifetime : \$150000
-----------------------------	---------------------

Environmental

Acoustic Level	45 dBA
----------------	--------

Heat Dissipation	225 Btu/h
------------------	-----------

Operating Altitude	0...10000 ft
Ambient Air Temperature For Operation	32...104 °F (0...40 °C)
Ambient Air Temperature For Storage	5...113 °F (-15...45 °C)
Storage Altitude	0...50000 ft (0.00...15240.00 m)
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

Control Panel	Multi-function LCD status and control console
Free Slots	1
Communication Port Support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge Energy Rating	680 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
Gtin	731304322795
Returnability	No
Country Of Origin	PH

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	12.99 in (33 cm)
Package 1 Width	23.23 in (59 cm)
Package 1 Length	12.99 in (33 cm)
Package 1 Weight	59.92 lb(US) (27.18 kg)

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
-----------------	---

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Environmental Certifications

✓ Energy Star® ENERGY STAR UPS V2.0 (USA)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)

California Proposition 65 **WARNING:** This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



Sales@UniLinkinc.com | www.UniLinkinc.com | 800.666.2980