



## APC Smart-UPS X, Line Interactive, 2200VA, Rack/tower convertible 2U, 100V-127V, 6x 5-15R+2x 5-20R NEMA, SmartSlot, Extended runtime

SMX2200RMLV2U

### Overview


<b>Presentation</b>	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
<b>Lead Time</b>	Usually Ships within 2 Weeks

### Main

<b>Main Input Voltage</b>	120 V
<b>Other Input Voltage</b>	100 V 110 V 127 V
<b>Main Output Voltage</b>	120 V
<b>Other Output Voltage</b>	100 V 110 V 127 V
<b>Kw Rating</b>	1980 W
<b>Rated Power In Va</b>	2200 VA
<b>Input Connection Type</b>	NEMA L5-30P
<b>Output Connection Type</b>	6 NEMA 5-15R 2 NEMA 5-20R
<b>Number Of Rack Unit</b>	2U
<b>Cable Length</b>	8 ft (2.44 m)
<b>Number Of Cables</b>	1
<b>Battery Type</b>	Lead-Acid battery
<b>Provided Equipment</b>	CD with software Documentation CD Installation guide Rack mounting hardware Rack Mounting brackets Rack Mounting support rails Removable support feet Smart UPS signalling RS-232 cable USB cable

### Batteries & Runtime

<b>Run Time</b>	<a href="#">View Runtime Graph</a>
<b>Efficiency</b>	<a href="#">View Efficiency Graph</a>
<b>Extendable Run Time</b>	1
<b>Included Battery Modules</b>	0

Battery Slots Empty	0
Typical Recharge Time	3 h
Rbc Quantity	1
Battery Life	3...5 year(s)
Replacement Battery	<a href="#">APCRBC117</a> 
Battery Charge Power (Watts)	233 W rated

## General

Number Of Power Module	1750
Number Of Power Module Filled Slots	0
Number Of Power Module Free Slots	0
Product Web Sub-Family	Extended run
Redundant	No

## Physical

Color	Black
Height	3.35 in (8.5 cm)
Width	17.00 in (43.18 cm)
Depth	26.26 in (66.7 cm)
Net Weight	84.77 lb(US) (38.45 kg)
Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Rack-mounted
Two Post Mountable	0
Usb Compatible	Yes

## Input

Efficiency At Full Load	70...153 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Harmonic Distortion	Less than 5%
Maximum Configurable Power In Va	2200 VA
Max Configurable Power (Watts)	1980 W
Transfer Time	2-4 ms 4ms typical : 8ms maximum
Topology	Line Interactive
Wave Type	Sine wave
Output Frequency (Sync To Mains)	50/60 Hz +/- 3 Hz sync to mains

## Conformance

<b>Product Certifications</b>	BSMI CSA NOM TÜV VCCI Class A
-------------------------------	-------------------------------------------

<b>Equipment Protection Policy</b>	Lifetime : \$150000
------------------------------------	---------------------

## Environmental

<b>Acoustic Level</b>	55 dBA
<b>Heat Dissipation</b>	268 Btu/h
<b>Operating Altitude</b>	0...10000 ft
<b>Ambient Air Temperature For Operation</b>	32...104 °F (0...40 °C)
<b>Ambient Air Temperature For Storage</b>	5...113 °F (-15...45 °C)
<b>Storage Altitude</b>	0...50000 ft (0.00...15240.00 m)
<b>Relative Humidity</b>	0...95 %
<b>Storage Relative Humidity</b>	0...95 %

## Communications & Management

<b>Control Panel</b>	Multi-function LCD status and control console
<b>Emergency Power Off (Epo)</b>	Yes
<b>Free Slots</b>	1
<b>Control Panel</b>	LED status display with on line : on battery : replace battery and overload indicators
<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

<b>Surge Energy Rating</b>	540 J
<b>Filtering</b>	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

## Ordering and shipping details

<b>Category</b>	11309 - APC RESALE PRODUCTS
<b>Gtin</b>	731304268567
<b>Returnability</b>	No
<b>Country Of Origin</b>	PH

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	9.57 in (24.3 cm)
<b>Package 1 Width</b>	34.21 in (86.9 cm)
<b>Package 1 Length</b>	23.46 in (59.6 cm)
<b>Package 1 Weight</b>	100.00 lb(US) (45.36 kg)
<b>Pallet Unit Layers</b>	2
<b>Pallet Layers</b>	4

# Contractual warranty

---

## Warranty

3 years repair or replace (excluding battery) and 2 years for battery, optional on-site warranties available, optional extended warranties available

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)



Energy Efficient   Take-back   Transparency   RoHS/REACH

## Resource performance

✓ Energy Efficient Product

---

✓ Take-Back Program Available

---

## Well-being performance

✓ Mercury Free

---

✓ Rohs Exemption Information   [Yes](#)

---

## Certifications & Standards

Reach Regulation   [REACH Declaration](#)

---

Eu Rohs Directive   Compliant with Exemptions

---

Environmental Disclosure   [Product Environmental Profile](#)

---

Circularity Profile   [End of Life Information](#)

---

**California Proposition 65**   **WARNING:** This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

---



[Sales@UniLinkinc.com](mailto:Sales@UniLinkinc.com) | [www.UniLinkinc.com](http://www.UniLinkinc.com) | 800.666.2980