



APC Smart-UPS, Line Interactive, 1500VA, Rackmount 2U, 120V, 6x NEMA 5-15R outlets, SmartSlot, AVR, LCD, W/L5-15P

SMT1500R2X122

Overview

Lead Time Usually Ships within 2 Weeks

Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	1000 W
Rated Power In Va	1440 VA
Input Connection Type	NEMA L5-15P
Output Connection Type	6 NEMA 5-15R
Number Of Rack Unit	2U
Cable Length	8 ft (2.44 m)
Number Of Cables	1
Battery Type	Lead-Acid battery
Provided Equipment	CD with software Documentation CD Installation guide Rack Mounting support rails Smart UPS signalling RS-232 cable USB cable

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Extendable Run Time	0
Included Battery Modules	0
Battery Slots Empty	0
Typical Recharge Time	3 h
Rbc Quantity	1
Battery Life	4...6 year(s)
Replacement Battery	APCRBC133
Battery Charge Power (Watts)	144 W rated

General

Number Of Power Module Filled Slots 0

Number Of Power Module Free Slots	0
Redundant	No
Variant Option	Twist-lock L5-15P Input Plug

Physical

Color	Black
Height	3.50 in (8.9 cm)
Width	17.01 in (43.2 cm)
Depth	17.99 in (45.7 cm)
Net Weight	63.14 lb(US) (28.64 kg)
Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Rack-mounted
Two Post Mountable	0
Usb Compatible	Yes

Input

Efficiency At Full Load	75...154 V adjustable 82...144 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Harmonic Distortion	Less than 5%
Maximum Configurable Power In Va	1440 VA
Max Configurable Power (Watts)	1000 W
Transfer Time	4ms typical : 8ms maximum
Topology	Line Interactive
Wave Type	Sine wave
Output Frequency (Sync To Mains)	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product Certifications	CSA
Equipment Protection Policy	Lifetime : \$150000

Environmental

Acoustic Level	46 dBA
Heat Dissipation	90 Btu/h
Operating Altitude	0...10000 ft
Ambient Air Temperature For Operation	32...104 °F (0...40 °C)
Ambient Air Temperature For Storage	5...113 °F (-15...45 °C)
Storage Altitude	0...50000 ft (0.00...15240.00 m)
Relative Humidity	0...95 %

Communications & Management

Control Panel	Multi-function LCD status and control console
Free Slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge Energy Rating	459 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

Ordering and shipping details

Gtin	731304294061
Country Of Origin	PH

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.88 in (25.1 cm)
Package 1 Width	23.74 in (60.3 cm)
Package 1 Length	23.39 in (59.4 cm)
Package 1 Weight	70.35 lb(US) (31.91 kg)

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)

California Proposition 65 **WARNING:** This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



Sales@UniLinkinc.com | www.UniLinkinc.com | 800.666.2980