

# SmartSource® Pro Elite

## The Secure Choice®



The SmartSource Pro Elite includes all the features that make a scanner ideal for teller and remote deposit capture applications, including a small footprint, durable design, high-speed capture, and industry-leading MICR accuracy and image quality on checks and other documents.



### ID CARD SCANNING

Features two-sided ID card capture using 600 dpi image sensors that produce high-resolution color or grayscale images.

### AUTOMATED CLEANING

Proper cleaning is the easiest – but most effective – way to prevent paper jams, double-feeds, image-quality problems, and unnecessary repairs on your scanners. Digital Check's automated cleaning feature makes it simple by giving a mechanical assist to your front-line operators.

An indicator light alerts users when it is time to clean. Use the Smart Button to activate cleaning mode, insert a cleaning card and the scanner performs a unique cleaning sequence that scrubs the track and cleans the sensors.

### KEY FEATURES & BENEFITS

- **Batch-Feed** - Scans up to 75 or 170 DPM
- **1-to-4-Line Inkjet Endorser**
- **Automated Cleaning with Smart Button Indicator**
- **ID Card Scan**
- **E13B and CMC7 MICR Recognition with Auto-Detect and integrated E13B Optical Recognition Assist**
- **Smart Button Combines Power Switch, Feeder Start/Stop, Cleaning Mode and LED Status Light**



### Fast & Powerful Batch-Feed Scanning

The Pro Elite is powerful enough for teller capture or branch capture, yet versatile enough for a small business. The Pro Elite features a 100-item input hopper and a top speed of up to 170 documents per minute, making it an ideal check scanner for medium to high-volume check scanning environments.



### Quality & Performance

The new SmartSource Elite series is a family of compact desktop check scanners, optimized for bank front-counter use as well as remote deposit capture. Like all scanners in the Digital Check® portfolio, the SmartSource Elite family provides industry-leading quality and performance.



### Industry-Leading Image & MICR Capture

The Pro Elite uses 600 dpi image sensors and applies thresholding to create high-resolution images resulting in superb CAR/LAR read rates. Our top-of-the-line MICR read heads coupled with optical recognition offer a proven and reliable defense against ambiguous characters and out-of-spec documents.



# SmartSource® Pro Elite

## Scanner Specifications



### Scanner Dimensions

Height: 6.99 in (17.8 cm)  
Width: 5.93 in (15.06 cm)  
Length: 8.66 in (22 cm)  
Weight: 4.7 lbs. (2.1 kg)

### Scan Speeds - Documents Per Minute (DPM)

USB Mode: Up to 75 or 170 DPM

### Document Input and Output Pockets

Entry Pocket: Up to 100 item hopper capacity  
Entry pocket automatically opens for ease of use  
Double-feed document detection  
Exit Pocket: Up to 150 items

### Document Handling

Document Height: 2.00 to 6.00 in (5.08 to 15.24 cm)  
Image Capture Height: Up to 4.25 in (10.80 cm)  
Document Length: 2.90 to 9.25 in (7.37 to 23.5 cm)  
Document Weight: 16 to 28 lb (60 to 105 gsm)  
Document Thickness: 0.0032 - 0.0058 in (0.081 - 0.147 mm)  
Front ID Input: ID cards and items up to 3.375 x 2.25 in (85.60 x 57.15 mm)  
ID Card Capture (supported by application)

### Inkjet Endorser

User-replaceable cartridge (600 dpi printing, 1-4 lines)  
Three (3) levels of print quality available (economy, standard, or premium)  
User-programmable text

### Image Sensor

Resolution: 600 dpi  
Light Source: Tri-Color LEDs

### Image Compression Standards

CCITT Group 4 (bitonal images)  
JPEG Baseline (gray level images)  
JPEG Compression (color images)

### MICR/OCR Recognition

E13B and CMC7 auto-sensing  
OCR-A, OCR-B, E13B  
Two (2) 0.50-inch OCR scan bands provided  
96 Characters per scan band  
MICR/OCR combined read

### Productivity Functions (Smart Button)

Multi-colored LED status light, combined power switch, feeder start/stop, clear document jam, and activate cleaning mode

### Connectivity

High-speed USB 2.0 cable and power supply included

### Application Programming Interfaces (API)

SmartPVA API  
Ranger Transport API (purchased separately from Silver Bullet Technology Inc.)

### Supported Operating Systems

#### SmartPVA for Windows

Windows 11, Windows 10 (32/64 bit)

**Ranger Transport API** (Please contact Silver Bullet Technology Inc. directly for information about Ranger's supported operating systems)

### Standard Warranty

One year pursuant to Digital Check Corp.'s limited product warranty

### Power Requirements

100-240 VAC @ 50/60 Hz  
Operating Power: 48 W  
Standby Power: 3 W

### Environmental

Operating Temperature: 60° - 90° F (15° - 32° C)  
Operating Humidity: 35 - 85% non-condensing

### Certifications

#### Safety:

UL, cUL, CE, BIS

#### Emissions:

FCC: Class A  
ICES-003  
CE  
VCCI

### Power Supply Efficiency:

DOE Level VI

RoHS Compliant

### Part Numbers

SSP1-ELITE75 (Pro Elite 75 DPM model)  
SSP1-ELITE155 (Pro Elite 170 DPM model)

### Stackable Receipt Printer Option

Digital Check offers the ReceiptNOW® Elite thermal printer, designed to fit underneath the Pro Elite, minimizing overall space requirements. The ReceiptNOW Elite printer can be configured with both Ethernet and USB connections.

