

TM-U375

Multifunction Printer



- Optimized features and small footprint perfect for teller stations
- Drop-in paper loading
- High-speed, logic-seeking print head
- Proven high reliability
- One-year warranty

The TM-U375 offers receipt, validation and slip printing all in one space-saving, easy-to-use multifunction printer.

Ideal for teller stations, the TM-U375 is supported by all major teller packages, so no software modifications are required, which means it's ready to go from day one.

The functionality you need

Epson's cost-effective TM-U375 multifunction printer can be used for a variety of applications. Designed to meet the need for high reliability and a small footprint at teller stations, it prints crisp, clean receipts and negotiable items, such as cashier's checks and money orders, at up to 5.4 lps. It also handles up to 16 lines of validation printing and up to 58 lines of slip printing quickly. It also can print an original plus one copy of a receipt and an original plus two copies of a slip.

Easy to use. Easy to maintain.

The TM-U375 offers many user-friendly features including drop-in paper loading and easy slip insertion. It also features an ASB (Auto Status Back) function that monitors the printer's status in real-time for easy upkeep and ongoing maintenance.

Designed to fit counter space

With measurements of just 7.3 x 12.9 x 5.7" (W x D x H), the TM-U375 is one of the smallest 1.5 station printers available which means you can use your limited teller counter space to its maximum advantage.

Proven reliability

The TM-U375 is broadly used by financial institutions and is supported by all the major teller software packages. In addition, it is one of the most reliable printers in its class with a MCBF of over 29 million lines.

Backed by the leader.

When you choose Epson's TM-U375, you can be sure you'll get the unsurpassed performance and reliability that Epson is known for. And it's backed by Epson's industry-leading service and support.

Epson TM-U375 Multifunction Printer

Printer Specifications

General	Print method	9-pin, serial impact dot matrix
	Print font	
	Font	5 x 9 / 7 x 9
	Column capacity	33 / 40 columns
	Character size	1.56 x 3.1mm (W x H)/1.24 x 3.1mm (W x H) {0.061 x 0.122"/0.049 x 0.122"}
	Character set	95 Alphanumeric, 32 International, 126 x 8 Graphic characters
Printer	Interface	RS-232C / Bi-directional parallel
	Data buffer	4KB/40 bytes
	Print speed	Approx. 3.5 lps (40 columns, 16 cpi) Approx. 5.4 lps (20 columns, 16 cpi)
	Paper dimensions	
	Receipts or Journal	76 ± 0.5 x diameter 83mm {2.99 ± 0.02 x diameter 3.27"}
	Slip	70 to 182 x 160 to 257mm (W x L) {2.76 to 7.17 x 6.30 to 10.12"}
	Validation	135 to 182 x 70 to 257mm (W x L) {5.31 to 7.17 x 2.76 to 10.12"}
	Paper thickness	
	Receipts or Journal	0.06 to 0.085mm [0.0024 to 0.0033"]/sheet (total thickness: 0.16mm [0.0062"] or less)
	Slip	0.09 to 0.12mm [0.0035 to 0.0047"]/sheet (total thickness: 0.09 to 0.31mm [0.0035 to 0.012"])
	Copy capability	
	Receipts or Journal	One original and one copy
	Slip	One original and two copies
	Inked ribbon	ERC-38 (purple, black)
	Ribbon life	4,000,000 characters (purple), 3,000,000 characters (black)
	Power supply	24 VDC ± 10%
	Power consumption	Approx. 1.4 A (mean)
	D.K.D. function	2 drivers
	Reliability	
	MTBF	180,000 hours
MCBF	29,000,000 lines	
Overall dimensions	186 x 327 x 145mm (W x D x H) {7.3 x 12.9 x 5.7"}	
Mass	Approx. 4.0 kg {8.8 lbs}	
Control Board	EMI standards	VCCI class A, FCC class A, CE marking
	Safety standards	UL, CSA

Inch values are approximate.

cpi: characters per 25.4mm (characters per inch)

lps: lines per second



Sales@UniLinkinc.com | www.UniLinkinc.com | 800.666.2980