

Outstanding Printing Power

The top printer model of our new ECOSYS series has it all: high-speed printing of up to 60 pages per minute. With a first print time of 4.5 seconds and a maximum capacity up to 2,600 sheets, you can print more and do so faster. It offers more than just performance but also unrivalled reliability. Thanks to the usage of long-life components the total cost of ownership and environmental impact are both exceptionally low.



ECOSYS P3260dn



A4 Monochrome printer

60 ppm for A4

1200 x 1200 dpi resolution

Specifications

GENERAL

KYOCERA ECOSYS Laser Monochrome Printer

Operation panel: 5 line LCD back lit display with alphanumeric keypad

Engine speed (pages per minute): Up to 60 pages A4 per minute in b/w.

Duplex print speed: up to 43 page per minute A4

Resolution: 1,200 x 1,200 dpi

Warm-up time: Approx. 25 seconds or less from power on.

Time to first page: Approx. 4.5 sec. or less.

CPU: ARM Cortex-A9 Dual core 1.2 GHz (+ ARM Cortex-M3 100MHz)

Memory: Standard 512 MB RAM, Max. 2.5GB + 128GB SSD

Standard interfaces: Standard interface: USB 2.0

(Hi-Speed), 2 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT), optional Wi-Fi (IEEE 802.11b/g/n), 1 eKUIO slot for optional internal print server or SSD hard disc, Slot for optional SD/SDHC Card.

Integrated accounting: 100 department codes Dimensions

(W x D x H): 410 mm x 416 mm x 363 mm.

Weight: Main unit approx. 15.5 kg.

Approx. 16.2 kg (with starter toner)

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption

Print - mode: 721 Wh

Ready mode: 11 Wh

Sleep mode: 0.7 Wh

Noise (Sound pressure level ISO 7779

measurement distance of 1 meter)

Stand by mode: 25.8 dB(A)

Printing: 56 dB(A)

Safety standards: TÜV/GS, CE; This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 100-sheet multi-purpose tray, 60 – 220 g/m², A4, A5, A6, B5, Letter, Legal, Folio,

Custom(70 x 140 to 216 x 356 mm), Banner paper up to 915 mm.

Standard universal paper cassette: 500 sheet, 60–120 g/m², A4, A5, A6, B5, Letter, Legal, Folio, Custom (105 x 148 to 216 x 356 mm). Max. input capacity with options: 2,600 sheets

Duplex functionality as standard: Double sided printing: A4, A5, B5, Letter, Legal, Custom (140 x 210 mm - 216 x 356 mm) 60–120 g/m²

Output capacity: 500-sheet-face-down with paper full sensor and optional 250-sheet-face-up with PT-320.

PRINT FUNCTIONS

Controller language: PRESCRIBE

Emulations: PCL6 (Sc/XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and Open XPS. **Operating systems:** All current Windows operating systems, MAC OS X Version 10.9 or higher, UNIX LINUX, as well as other operating systems on request.

Fonts/barcodes: 93 outline fonts (PCL6/KPDL 3), 8 fonts (Windows), 1 Bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417) **Print features:** PDF Direct Print, IPP printing,

e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, Encrypted PDF Direct Print.

Mobile printing support: KYOCERA Mobile

Print app for iOS and Android; Mopria, Google Cloud Print, Airprint, Direct Wi-Fi (opt).

CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19752.

TK-3200 Toner Kit: Microfine toner black for 40,000 pages A4

TK-3190 Toner Kit: Microfine toner black for 25,000 pages A4

TK-3170 Toner Kit: Microfine toner black for 15,500 pages A4

TK-3160 Toner Kit: Microfine toner black for 12,500 pages A4,

Capacity of starter toner is 11,000 pages A4

OPTIONS

PF-3110 Paper feeder (max. 4 units): Max. 500 sheets, 60 - 120 g/m²; A4, A5, B5, Letter, Legal, Custom (92 x 162 mm - 216 x 356 mm)

PF-3100 Bulk paper feeder and PB-325 Printer base: Max. 2,000 sheets, 60 - 120 g/m²; not to be combined with PF-3110

CB-360W Cabinet: Wooden desk with storage capacity, Approx. 380 x 411 x 508 mm (WxDxH)

CB-365W Cabinet: Wooden desk with storage capacity, Approx. 380 x 411 x 254 mm (WxDxH)

CA-3100: Caster stand

PT-320 Paper tray: 250-sheet face-up output tray

Memory upgrade: MD3-1024, MDDR3-2G, DDR3, 1GB/2GB

Storage Devices: HD-6 SSD hard disk: 32GB and HD-7 SSD hard disk: 128 GB for easy document management.

SECURITY

Embedded data encryption and data overwrite (DSK) when optional SSD, HD-6 or HD-7 are installed

UG-33: ThinPrint support

USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available

Optional interface:

IB-50: Gigabit Ethernet:

10BaseT/100BaseTX/1000BaseT (RJ45).

IB-51: Wireless Lan (802.11b/g/n).

IB-36: Wireless Lan (802.11b/g/n) with Wi-Fi Direct.

IB-32B: IEEE1284 interface.

WARRANTY

2-year carry-in warranty as standard. Kyocera guarantees the drum and developer for 3 years or 500,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions.

ECOSYS stands for ECOlogy, ECONomy and SYSTEM printing. With long-life components, ECOSYS devices maximise durability and minimise total cost of ownership. The cartridge-free system means that you only need toner. The modular design concept allows workflow enhancing functions while integrated system software provides crossnetwork compatibility. This product is compliant with Energy Star.



KYOCERA Document Solutions Belgium N.V.
Sint-Martinusweg 199-201, 1930 Zaventem, Belgium
Tel +32 (0)2 720 92 70 – info@dbe.kyocera.com



Kyocera Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



Sales@UniLinkinc.com | www.UniLinkinc.com | 800.666.2980

KYOCERA Document Solutions Partner

SEPTEMBER2019DSECOSSYP3260DN/VER1.0

kyoceradocumentsolutions.be